



### SPECIFICATION

Double Jumbo Roll Toilet Roll Holder shall hold two (2) 229mm diameter rolls of 76mm diameter or 57mm diameter core tissue. Unit cabinet, door and mounting plate shall be fabricated of alloy 18-8 stainless steel, grade 304, 18 gauge with a No. 4 satin finish and shall be protected during shipment with a PVC film easily removable after installation. Door shall be of drawn one piece seamless construction with integral rigidizing ribs and shall be provided with two (2) tissue level viewing slots. Door shall be hung on heavy duty stainless steel pivot hinges and shall be held closed by a tumbler lock keyed to other ASI JD MacDonald washroom equipment. Dispensing mechanism shall be fabricated of high impact chemical and flame retardant ABS. Unit shall accommodate smaller core size rolls by removing the core adapters. When one roll is depleted, other roll shall be selected by shifting over panel lever at bottom of unit. Unit shall automatically reset to first roll during maintenance access.

### INSTALLATION

For general utility surface mount unit within 305mm of front of toilet from centre line and 787mm above finished floor from bottom of unit with five (5) screws (supplied by others) through mounting holes provided. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.


### OPERATION

Two (2) 229mm OD jumbo rolls of toilet tissue are mounted over 76mm ID core adapters. Two (2) 57mm ID core rolls may be used by removing the core adapters. Whenever one toilet roll is depleted, the other roll is selected by shifting over the lever at the bottom of the unit. Viewing slots continuously reveal tissue level. Key locked door prevents unauthorized access or removal. Tissue supply is replenished on a cycle determined by maintenance needs.

### WARRANTY

One year.

**Double Jumbo Toilet Roll Holder** shall be Model No. 10-0040 as supplied by ASI JD MacDonald.

 All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

