



SPECIFICATION

Recessed Paper Towel Dispenser and Waste Bin shall hold and dispense 600 C-fold, 800 multi-fold or 1100 single-fold paper towels and shall have a waste capacity of 26 litres. Unit shall be fabricated of alloy 18-8 stainless steel, grade 304, 22 gauge with No. 4 satin finish and be protected during shipment with a PVC film easily removable after installation. Adjustable guide shall be provided to allow dispensing of multi-fold or C-fold paper towels. Face trim shall be one piece construction with no miters or welding and shall be 25mm wide and have 6mm square return to wall. Cabinet shall have no exposed fastening devices or spot welded seams. Doors shall be double pan construction with No-Flex core and shall be mounted to cabinet body on 5mm diameter heavy duty stainless steel multi-staked piano hinges. Dispenser and disposal doors unit shall have tumbler locks keyed alike to other ASI JD MacDonald washroom equipment.

INSTALLATION

Unit is mounted in wall recess with No. 10 self tapping screws (supplied by others) through concealed mounting holes. Note that top of rough wall opening is 19mm below top of unit. Rough Wall Opening (RWO) required is 290mm x 1360mm x 160mm. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.


OPERATION

Paper towels are manually withdrawn through dispensing slot. Dispenser is refilled by unlocking door and replacing towels for an empty or partially empty unit. Dispenser supply is replenished on cycle determined by maintenance needs.

WARRANTY

One year.

Recessed Paper Towel Dispenser & Waste Bin shall be Model No. 10-0467 as supplied by ASI JD MacDonald.

 All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

