



SPECIFICATION

Semi-Recessed Paper Towel Dispenser with Waste Receptacle shall hold and dispense 500 standard multi-fold or 400 standard C-fold paper towels and shall have a waste capacity of 26 L. Dispensing of multi-fold or C-fold paper towels shall not require an additional adapter. Cabinet, door, dispenser and waste receptacle (WR) shall be type 304 stainless steel alloy 18-8. All exposed surfaces shall have satin finish and shall be protected during shipment by PVC film easily removable after installation. Cabinet shall be 20 gauge with a 16mm wide perimeter trim to lay flush against wall and shall have no exposed fastening devices or visible seams. Full-face door shall be 18 gauge, fabricated from one piece with no miters or seams on face and shall have 25mm square returns to the wall. Door shall be attached to cabinet body with a full length 4.8mm diameter stainless steel multi-staked piano hinge and shall be held closed with one (1) tumbler lock on left side panel inside lower window, keyed alike to other ASI JD MacDonald washroom equipment. Towel dispensing slot shall have a fully hemmed-in rolled edge for snag-free dispensing and user safety. WR shall have piano-hinge mounted closed top with spring-hinge closed flap door and hemmed edges for safety. Structural assembly of all cabinet components shall be of welded construction.

FINISH

Satin finish stainless steel 304 grade

INSTALLATION

Unit is mounted in wall recess using № 10 [M5] self-tapping screws (by others) through concealed mounting holes provided. Note that top of RWO is 10mm below top of unit. The unit must be at 100mm from the finished floor level to comply with Australian Disabled Standards 1428.1 & 1428.2.

ROUGH WALL OPENING (RWO)

408mm (W) x 1494mm (H) x 127mm (D).

OPERATION

Paper towels are manually withdrawn through dispensing slot and feed properly until depleted. Unit will continue to feed towels properly when correctly reloaded with a partial load in place. Refill dispenser by unlocking door and replacing towels for an empty or partially empty unit. Dispenser supply is replenished and waste container is emptied manually on cycles determined by maintenance needs. Locking full-face door over compartments prevents unauthorized access or removal. Full cover and spring-hinge flap door on WR prevents unsightly overloads.

OPTIONS


10-764671-SR2 small cavity trim for semi recessed installations

10-764671-SM trim for surface mount installations

WARRANTY

The ASI JD MacDonald Select Classic 2in1 G2 comes with a 1 year warranty.

Select Classic 2in1 G2 shall be Model No. 10-64671-A Paper Towel Dispenser & Waste Bin as manufactured by ASI JD MacDonald.

 All ASI JD MacDonald accessible compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

SELECT CLASSIC
Select Classic 2in1 G2
Model No. 10-64671-A

