

Surface Mounted Baby Change Station

Model No. 10-9017-9

Date: January 2016



*Recessed Unit Shown Above

FEATURES

Surface Mounted Vertical SS Clad Baby Change Station includes a concealed damped gas spring mechanism for smooth, safe and effortless opening and closing using one hand. No parts of the operating mechanism shall be accessible to provide a tamperresistant and pinch proof user environment. Unit provides a bed-liner dispenser that may be easily converted to a multi-fold towel dispenser with no adapters. Graphic and instructions in four languages on interior back. Adjustable two-part child protection safety-strap mounted with concealed fasteners on high walls of cradle. Entire unit shall be assembled of completely sealed components to provide easy cleaning and no penetration zones to harbor microbes or bacteria. One integral heavy-duty bag hook. Unit shall mount on standard stud wall dimensions and with proper anchoring may mount on all suitable wall constructions. Mounting fasteners shall be concealed after installation using colour matched recess plug-covers supplied. Unit shall be recyclable at end of usable life to help reduce global waste.

INSTALLATION DETAILS

Unit is surface mounted using hardware supplied through recessed mounting holes provided. Hardware kit supplied has fasteners suitable for metal or wood stud walls in dry locations and general hollow wall construction where adequate substrate strength is obtained. Fasteners and anchors for masonry walls are not provided.

Wall reinforcement must be suitable to sustain transfer of maximum unit loading.

- 1. Locate wall studs at 16" [406] OC for fastening the station. If two wall studs cannot be used, use two screws into ONE stud and drill pilot holes and install toggle fasteners securely in the wall at non-stud location.
- **2.** Attach unit to wall studs with four 1/4" x 3" long Phillips pan head self-tapping screws through flat washers.
- 3. Where wall studs are not available attach with four 1/4" 20 x 3" pan head bolts with flat washers into toggles or expansion nuts.

SPECIFICATION

Unit supports a static load of up to 136.1kg (tested in excess of 158.8kg) when properly installed in accordance with the Installation and Operating Instructions supplied with the unit.

MATERIAL

High density polyethylene body (HDPE) and satin finished 304 stainless steel.

OPTIONS

- Recessed unit available (Part No. 10-9017)
- Box of 500 liners (Part No: LCR)
- Replacement strap (Part No: 10-9014-14159)

WARRANTY & PRODUCT LIABILITY

ASI JD MacDonald Baby Change Stations are guaranteed against defective materials and faulty workmanship for 5 years from date of purchase, subject to being installed and maintained in accordance with the Installation and Operating Instructions supplied with the unit.

A \$10 million product liability insurance policy is maintained on all baby change stations.

Surface Mount Baby Change Station Stainless Steel Clad Vertical shall be Model No. 10-9017-9 as supplied by ASI JD MacDonald.

All ASI JD MacDonald accessible compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.



Surface Mounted Baby Change Station Stainless Steel Clad Vertical Model No. 10-9017-9

DIM'S INCH [MM]



