



SPECIFICATION

Royal™ Collection Surface Mounted Sanitary Waste Bin shall hold 3.8 litres of waste material. Cabinet full top cover shall be drawn seamless and receptacle body shall be formed seamless and shall have bowed front face and gently radiused front vertical edges to provide added strength and complimentary appearance for modern washroom aesthetics. Full top door shall be 22 gauge type 304 stainless steel alloy 18-8 with satin finish and shall be attached to the cabinet at back with a concealed full-width 9/64" diameter (Ø3.5) heavy-duty stainless steel multi-staked piano hinge. Structural assembly of body and door components shall be of welded construction. Unit shall be 22 gauge type 304 stainless steel alloy 18-8 with satin finish and shall have contoured cover finger lift relief and be protected during shipment with PVC film that is easily removable after installation. Waste bin full top edge is hemmed with return to inside for user and service safety. Waste bin shall have no exposed fastening devices or spot-welded seams. Waste bin shall be screw mounted to wall or partition through concealed keyhole slots provided through rear panel.

INSTALLATION

Hang unit on wall with two (2) pre-installed № 10 x 32mm self-tapping pan head screws (by others) through the mounting keyhole slots provided into suitable wall reinforcements (by others) or two (2) pre-installed № 10 x 19mm self-tapping pan head screws (by others) through the mounting keyhole slots provided into metal partition. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.


OPERATION

User lifts lid to deposit waste material. Maintenance schedule determines trash removal cycle. Unload unit by either removing the disposable wax paper liner bag (by others) or unhooking the unit from the mounting screws and inverting to empty into appropriate bulk collection container.

WARRANTY

One year.

Surface Mounted Sanitary Waste Bin shall be Model No. 10-20852 as supplied by ASI JD MacDonald.

 All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

