



SPECIFICATION

Designed for the safety, security and convenience of the physically disabled. Easy to install on most building surfaces. Drop down Grab Rail shall be shall be type 304 stainless steel alloy 18-8. Tubing shall be 32mm diameter x 18 gauge (1.2mm). Rail is adjustable to 3 positions.

OPTIONS

With Toilet Roll Holder: **JDM-GDD-TRH**.

ASI JD MacDonald can supply custom Grab Rails to satisfy any unique application (POA).

FINISH

All exposed surfaces shall have a Satin finish.


RECOMMENDED INSTALLATION

To comply with Australian Standards AS 1428.1, grab rails must be fastened a minimum distance of 800mm from the floor, with 600mm of clear space above the rail and to withstand a force of 1100N at any point from any direction.

WARRANTY

Grab Rail products distributed by ASI JD MacDonald are guaranteed to be free from defective materials and workmanship for 12 months from the date of purchase, subject to product being installed and maintained in accordance with the Installation and Operating instructions (fixings supplied by others).

Grab Rail JDM-GDD shall be Model No. JDM-GDD as supplied by ASI JD MacDonald.

 All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

